

Lifeloc FC 20

Professional Breath Alcohol Tester



Specifications

- Sensor – Advanced 1” Electrochemical Fuel Cell
- Pump – Automatically actuated electronic pump system. No cocking required
- Units of Measure – BAC Standard. Can be set to other common units of measure.
- Response Time – Immediate on Negatives, under 10 seconds on Positives.
- Recovery Time – Immediate on Negatives, under 30 seconds on Positives.
- Accuracy – DOT Approved at +/- .005 BAC to .100 BAC, +/- 5% from .100 to .400 BAC.
- Operating Temperature Range – 0 C to 55 C
- Self Diagnostics – Programmed self-check assures unit is operational upon power-up.
- Size – 66 x 127 x 33 mm
- Weight – 255 grams
- Warranty – One year limited warranty ; parts and labour
- Detection Range - .000 to .600 BAC
- Power – 4 AA alkaline batteries. 160 hours of operation which equates to +/- 5000 tests per battery set.
- Display – 1.75” x .85” viewing area graphic LCD. Extended temperature range. Automatic back light for night time use.
- Mouthpieces – One-piece, individually wrapped, disposable. Quick snap-on design directs exhausted breath away from operator.
- Computer Interface – DataTrak™ software downloads test results directly to your PC. Sort, print, archive and chart results.
- Data Management Solutions – Multiple data entry fields for unique Subject ID, User ID or Location Information.
- Memory – 500 Test Memory
- Printing Capabilities – Portable Thermal Printer or PC printing with DataTrak™.